

DayCor® UVollé

UVollé-SX | UVollé-VX



HANDHELD CORONA CAMERA



UVollé-SX & UVollé-VX slender handheld models of corona cameras offer a cost effective combination of performance and price. UVollé cameras are used to detect, test, record and display corona partial discharges. The embedded benchmarked proprietary DayCor® technology guarantees accurate and reliable data provision of corona occurrences. UVollé cameras are designed ergonomically to match outdoors & indoors inspection conditions, and fit operators' requirements for safety and comfort: low weight, physical dimensions, good hands grip, high clarity of the presented data, easy access to functions, easy to reach buttons, large buttons. UVollé offers more than 7 hours ongoing continuous battery run time operation without overheating.

Used for predictive maintenance by: electrical utilities, metal fabricators (FAB), heavy industries, mines, refineries, data centers, workshops, electrical contractors and owners of high and medium voltage assets

- >> Shoot, store & playback video and stills
- >> Visible & UV zoom
- >> RIV Sensitivity of 3.6 dβμV (RIV) @ 1MHz @ 10m
- >> Auto and manual focus
- >> More than 4 hours battery run time
- >> 5" WVGA sun readable backlight TFT LCD 1000 cd/m²

- >> Built-in powerful led flashlight
- >> Corona event counting
- >> IP 54
- >> GPS, Temperature & Humidity interfaces
- >> Tested & Certified Sensitivity to UV
- >> Continuous operation without over heating

SLENDER AND LIGHT

Light in weight with a slim profile that fits a hand grip, UVollé can be operated with a single hand. Carried by a padded shoulder strap.

CORONA PINPOINTING

With overlapping accuracy of 1 miliradian the merged channels (UV & visible) pinpoint the emitting sources. UVollé's excellent detectors enable presenting the original occurrences of corona anchored to the emitters.

UV EVENTS COUNTER

The intensity of the detected corona is presented as a count of the encountered UV events per time unit. Handy for research, comparisons and reports.

USER FRIENDLY

User friendly interface and easy to operate: turn-on, aim, shoot and store video clips and still pictures. Camera preferred default settings can be personalized.

RECORDING VIDEO, STILLS, AUDIO & PLAYBACK

Videos and pictures are recorded & stored on a removable flash card, and can be played back. Voice annotations can be recorded and used for documentation and reporting.

DAYCOR® TECHNOLOGY INSIDE



DayCor® most sensitive technology is implemented providing full solar blindness and high sensitivity to UV [Registered Patent EP1112459B1]. Frame integration is also optional as a way to enhance signals.

DELUXE REFLECTIVE 5" LCD

A wide 5" high resolution VGA 800 x 480 pixels, LCD, with 1000 cd/m² sun readable, adjustable power backlight, delivers sharp and vivid imaging of the inspected scenes.

INTEGRATED FLASHLIGHT

An integrated LED Flashlight with 2 levels of brightness enables inspecting interior parts of cabinets and darker rooms, without affecting the corona count.

SX VX**TECHNICAL SPECIFICATIONS****UV - OPTICAL PROPERTIES**

✓	✓	Minimum Discharge Detection	1 pC @ 10m (real test by RWE certified: DIN EN 60270 (VDE 0340):2001-08)
✓	✓	Minimum RIV Sensitivity	3.6 dBµV @ 1MHz @ 10m (real test by RWE certified: NEMA 107-1987)
✓	✓	Minimum UV Detection	3x10 ⁻¹⁸ watt/cm ²
✓	✓	Spectral Range	240-280nm
✓	✓	Detector Life Span	No degradation
✓	✓	UV Frames Integration	On Off

VISIBLE - OPTICAL PROPERTIES

✓	✓	Minimum Visible Light Sensitivity	0.1 Lux
✓	✓	Spectral Range	Visible range, Full color
✓	✓	Zoom	10x Optical, 12x Digital

IMAGING PERFORMANCE

✓	✓	Field of View (HxV)	6.4° x 4.8°
✓	✓	Focus	Full manual and auto focus for UV and visible channels
✓	✓	Focus Range for UV & Visible	1.5m 4.9ft - infinity (0.5m 1.6ft with close up lens)
✓	✓	UV Zoom	3 steps

DISPLAY

✓	✓	Image Modes	Visible/UV/Combine
✓	✓	UV/Visible Overlay Accuracy	Deviation < 1 miliradian
✓	✓	Display	5" Color sun readable TFT LCD WVGA (800X480 pixels) 1000 cd/m ²
✓	✓	Status Indicators	Battery, Memory, Gain, Counting, Date, Selected functions, Focus, Inspection mode , corona color, GPS (access.), Temp & Humidity(access.)
✓	✓	User Configuration Settings	Corona color (White, Red , Green, Yellow, Purple) Time, Sleep Mode, LI, LCD Parameters

CONTROL & OPERATION

✓	✓	Working Modes	Real time, standby, off
✓	✓	Continuous Operation	Unlimited. No overheating
✓	✓	Control Inputs	Keypad and hot keys
✓	✓	Mounting Point	Standard 1/4" x20 thread tripod mount
✓	✓	Flashlight	Built-in, Led, 2 steps

MEDIA CAPTURE & STORAGE

	✓	Video Capture	
✓	✓	Stills Capture	
✓	✓	Digital Storage	Removable SD card
	✓	Video Format	AVI
✓	✓	Stills Format	BMP
	✓	Audio	External microphone
✓	✓	Playback	Still pictures Video and still pictures

OUTPUT INTERFACES

✓	✓	Video Out (NTSC, Standard), GPS, Temp & Rel Humidity Meter	
---	---	--	--

POWER SUPPLY

✓	✓	Battery type	Li-Ion
✓	✓	Battery Run Time	4 hours
✓	✓	External Supply	DC 7V
✓	✓	Nominal Power Consumption	6.5-10.5VDC, 10 Watts

COMMUNICATION

✓	✓	Interface	RS232
---	---	-----------	-------

PHYSICAL CHARACTERISTICS

✓	✓	Size (LxWxH)	29x13.6x8.5 cm 11.4"x5.4"x3.3"
✓	✓	Weight	1.39Kg 3lb

ENVIRONMENT

✓	✓	Operating & Storage Temp Range	-20°C up to +55°C -4°F up to +131°F
✓	✓	Encapsulation	IP54

ACCESSORIES

Close-up & Wide FOV Lenses; CoronaWise SW; Temp.& Rel Humidity Meter; GPS; Wired Remote control; Insepection Guide

Specifications are subject to changes without notice. Imagery used for illustration purposes only. Copyright Ofil Ltd. V.16.0